

SOCIAL DISTANCING SIGNS

CALL TO ORDER: 800-989-1695



Horizontal / Floor application



Vertical / Door application



These vinyl signs convey social distancing rules at your facility. Place on floors, walls, or doors - anywhere people gather as they wait. Bright colors and bold messages are sure to be noticed. Easy installation and removal.



SOCIAL DISTANCING SIGNS

High performance PVC signs with clear, semi-permanent adhesive.

STANDARD SIZES (mm nominal)

Product	Part #	Size	Description	Price
	WVPN-RED/ WHT-11X11- PWH-C	11" x 11" 280 x 280 mm	"PLEASE WAIT HERE" with Cart Package of 5	\$99.95
	WVPN-RED/ WHT-11X11- PWH	11" x 11" 280 x 280 mm	"PLEASE WAIT HERE" Package of 5	\$99.95
	WVPN-RED/ WHT-11X11- YMH	11" x 11" 280 x 280 mm	YOUR MESSAGE HERE Custom Message Package of 5	\$99.95
	WVPN-RED/ WHT-23X23- WPSD	23" x 23" 584 x 584 mm	"WE PRACTICE SOCIAL DISTANCING" Package of 5	\$214.95
	WVPN-RED/ WHT-23X23- SHP-S	23" x 23" 584 x 584 mm	"STAND HERE PLEASE" Red with White Shoe Prints Package of 5	\$214.95
	WVPN-RED/ WHT-11X11- KSFA	11" (280 mm), Round	"KEEP 6 FEET APART" Red with White Shoe Prints Package of 5	\$99.95
	WVPN-BLU/WHT- 11X11-SNT	11" (280 mm), Round	Blue with White Shoe Prints/No Text Package of 5	\$99.95
	WVPN-YLW/BLK- 11X11-FMR	11" (280 mm), Round	Yellow with Black Letters "FACE MASK REQUIRED/ MASCARA REQUERIDA" Package of 5	\$99.95
	WVPN-GRN/ WHT-11X11-ANT	11" (280 mm), Round	Green with White Arrow/No Text, Package of 5	\$99.95

CALL TO ORDER:
800-989-1695

- Communicate your social distancing rules where people tend to congregate
- Floor application to tile, smooth concrete, finished wood, highly polished marble
- Vertical application to glass doors, metal doors, windows
- Semi-permanent self-adhesive
- Custom wording available
- One-year warranty against manufacturer defects

Technical Data

Minimum Application Temperature	46°F
Thickness (without liner and adhesive)	2-mil
Dimensional Stability (FINAT TM-14)	Adhered to steel, no shrinkage in cross direction; In length, <.006"
Temperature Resistance	Adhered to aluminum, -58°F to +230°F, no variation
Fire Behavior (DIN 75200)	Adhered to steel, self-extinguishing
Fire Rating	ASTM E 84-07 Class "A"
Adhesive Power (FINAT TM-1, after 24 h, average)	Adhered to stainless steel: 4.1 lb/in

Preparing the surface

The high-quality special adhesives used for Safeguard Social Distancing Signs create an excellent bond with just about any clean, smooth, and weatherproof surface which is free of grease, wax, and silicone. Prior to applying, clean the surface thoroughly with isopropanol and wipe it dry with a cloth. Gas bubbles may form between the film and the surface if any solvent residue remains as a result of improper cleaning.

It is important that the surfaces receiving the designs be thoroughly cleaned. Be sure to allow sufficient time for the solvent to evaporate after cleaning.

Removability

Environment and surface temperature must be at least 68° F (20° C) before these films can be removed. Using a knife, first cautiously lift up one corner of the film. Then slowly draw the film from the surface at a 180° angle. Heating the film with a hot-air gun while pulling makes removal considerably easier.

Contact Safeguard Technology for more information today.



SAFEGUARD TECHNOLOGY INC.

330.995.5200 | 800.989.1695 Toll-Free in the U.S. and Canada
Email: info@safeguard-technology.com
www.safeguard-technology.com

© Copyright 2020 SAFEGUARD TECHNOLOGY INC.
SAFEGUARD® Covers, Hi-Traction®, HiGlo-Traction®, Roll-Traction®, and Valu-Traction® are registered trademarks of SAFEGUARD Technology Inc.